

CRYSTAL FILTER SERIES

455 KHz Crystal Filters

Model No	Pass Band (60dB:Hz)	Stop Band (60 dB:Hz)	Att Guran (dB)	Ripple(dB)	Loss(dB)	Case
	min	max	min	max	max	
455H100	± 50	± 200	80	1	7	FK-2 or FK-3
455H250	± 125	± 300	80	2	6	
455H400	± 200	± 500	80	2	6	
455H500	± 250	± 600	80	2	5	
455H1.0	± 500	± 900	70	2	5	
455H1.8	± 900	± 1600	70	2	5	
455H2.1	± 1100	± 1900	70	2	5	
455H2.4	± 1200	± 2100	70	2	5	
455H2.7	± 1350	± 2400	70	2	5	
455H3.2	± 1600	± 2800	70	2	5	
455H6.0	± 3000	± 6000	70	2	7	
455F100	± 50	± 250	80	1	6	
455F250	± 125	± 400	80	2	5	
455F500	± 250	± 800	80	2	5	
455F1.0	± 500	± 1100	70	2	7	
455D150	± 75	± 600	70	1	4	
455D300	± 150	± 1000	70	2	4	
455D600	± 300	± 1800	70	2	4	

*Standard Terminating Impedance: 2K //30pF (50-5K is also available.)

