

SMD-407F Series

Miniature 4 Pole SMD MCF

Model	Freq	Pass band Width		Attenuation Width		Guaranteed Attenuation		Rippl e	Loss	Terminating Impedance
	MHz	dB	KHz	dB	KHz	dB	KHz	Max	Max	//pF
44S11B	44.25	3	± 5.50	35	± 20.0	70	-910	1.5	3.0	600//2.5
44S13B	44.25	3	± 6.50	22	± 12.5	70	-910	1.0	3.0	430//6.0
45SS7.5	45.00	3	± 3.75	30	± 12.5	80	-910	1.0	4.0	350//6.5
45SS20	45.00	3	± 10.0	25	± 25.0	80	-910	1.0	3.0	500//2.5
45SS15	45.05	3	± 7.50	35	± 25.0	80	-910	1.0	3.0	650//3.0
45S15B	45.10	3	± 7.50	35	± 25.0	70	-910	1.5	3.0	650//2.2
47S15B	47.25	3	± 7.50	35	± 27.0	70	-910	1.0	3.0	800//1.7
70S20B	70.05	3	± 10.0	20	± 25.0	70	-910	1.0	4.5	2500//1.0
73SS13	73.35	3	± 6.50	30	± 20.0	65	-910	1.0	4.0	1700//0.6

All specifications are subject to change without notice.

